



Sample photo

Order symbol: PC 100/100 HT
Product nbr: 6011903
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074022295
EI. number:
 Finland 3420423
 Denmark 8212022344
 Italy 7352030
 Sweden 2535615

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:		L	W	H	Rating:
mm:		130	80	100	Ingress Protection (EN 60529): IP 66/67
inch:		5.1	3.1	3.9	Impact Resistance (EN 50102): IK 08
Materials:					
Material:		PC			Electrical insulation: Totally insulated
Base colour:		RAL 7035			Halogen free (DIN/VDE 0472, Part 815): Yes
Cover colour:		Smoked grey			UV resistance: UL 508
Cover screws material:		Polyamide			Flammability Rating (UL 746 C 5): UL 94 5V
Cover screws colour:		Black			Glow Wire Test (IEC 695-2-1) °C: 960
Gasket material:		TPE			NEMA Class: NEMA 1, 4, 4X, 6
Temperatures:					
Short term:		-40 ... 120 °C			Certificates:
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
MIV 100		Mounting plate			Germanischer Lloyd (GL)
MIN 5		DIN-15 Mounting rail			Underwriters Laboratories
MIN 10		DIN-15 Mounting rail			Det Norske Veritas
MIV 5		DIN-35 Mounting rail			Fimko
MIV 10		DIN-35 Mounting rail			Europe EN 50298 1998
FP A 100/130		Front plate			UL Canada
HFP 130		Front plate hinge series			Gost R

