



Sample photo

Order symbol: PCT 233009
Product nbr: 7022871
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074003829
EI. number:
 Finland 3423544
 Denmark 8212003017
 Italy 7302060

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

Dimensions:		L	W	H	Rating:	
mm:		230	300	87	Ingress Protection (EN 60529): IP 66/67	
inch:		9.1	11.8	3.4	Impact Resistance (EN 50102): IK 08/07	
Materials:					Electrical insulation: Totally insulated	
Material:		PC			Halogen free (DIN/VDE 0472, Part 815): Yes	
Base colour:		RAL 7035			UV resistance: UL 508	
Cover colour:		Clear transparent			Flammability Rating (UL 746 C 5): UL 94 5V	
Cover screws material:		Stainless steel			Glow Wire Test (IEC 695-2-1) °C: 960	
Gasket material:		Polyurethane			NEMA Class: NEMA 1, 4, 4X, 12, 13	
Temperatures:					Certificates:	
Short term:		-40 ... 120 °C			Underwriters Laboratories	
Continuous:		-40 ... 80 °C			Fimko	
Short term:		-40 ... 250 °F			Europe EN 50298 1998	
Continuous:		-40 ... 175 °F			UL Canada	
					Gost R	
Accessories:						
TM 2330		Mounting plate				
TRM 0816		DIN-15 Mounting rail				
TRH 1216		DIN-35 Mounting rail				
TRH 2330		DIN-35 Mounting rail				

