



Sample photo

**Order symbol:** AB 122008  
**Product nbr:** 7083760  
**Description:** Enclosure, ABS  
**Remarks:** Grey cover

**EAN:** 6418074003553  
**El. number:**  
 Finland 3423488  
 Denmark 8212003525  
 Italy 7311045

**Including:** Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

| Dimensions:                   |  | L   | W   | H  | Rating:  |
|-------------------------------|--|---|-----|----|--|
| mm:                           |  | 120   | 200 | 75 | <b>Ingress Protection (EN 60529):</b> IP 66/67 |
| inch:                         |  | 4.7   | 7.9 | 3  | <b>Impact Resistance (EN 50102):</b> IK 07     |
| Materials:                    |  |   |     |    |  |
| <b>Material:</b>              |  | ABS   |     |    |  |
| <b>Base colour:</b>           |  | RAL 7035  |     |    |  |
| <b>Cover colour:</b>          |  | RAL 7035  |     |    |  |
| <b>Cover screws material:</b> |  | Stainless steel                                   |     |    |  |
| <b>Gasket material:</b>       |  | Polyurethane                                      |     |    |  |
| Temperatures:                 |  |   |     |    |  |
| <b>Short term:</b>            |  | -40 ... 80 °C                                     |     |    |  |
| <b>Continuous:</b>            |  | -40 ... 60 °C                                     |     |    |  |
| <b>Short term:</b>            |  | -40 ... 175 °F                                    |     |    |  |
| <b>Continuous:</b>            |  | -40 ... 140 °F                                    |     |    |  |
| Accessories:                  |  |   |     |    |  |
| TM 1216                       |  | Mounting plate                                    |     |    |  |
| TM 1220                       |  | Mounting plate                                    |     |    |  |
| MIV 10                        |  | DIN-35 Mounting rail                              |     |    |  |
| TRH 1220                      |  | DIN-35 Mounting rail                              |     |    |  |
|                               |  | <b>Electrical insulation:</b> Totally insulated   |     |    |  |
|                               |  | <b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes |     |    |  |
|                               |  | <b>Flammability Rating (UL 746 C 5):</b> UL 94 HB |     |    |  |
|                               |  | <b>Glow Wire Test (IEC 695-2-1) °C:</b> 650       |     |    |  |
|                               |  | <b>NEMA Class:</b> NEMA 1, 4, 4X, 12, 13          |     |    |  |
| Certificates:                 |  |   |     |    |  |

