



Sample photo

**Order symbol:** P 404012  
**Product nbr:** 7094450  
**Description:** Enclosure  
**Remarks:** Polyester

**EAN:** 6418074004444  
**El. number:**  
 Finland 3423681  
 Denmark 8212005714  
 Italy 7331065  
 Sweden 2536239

**Including:** Base, cover with EPDM gasket and stainless steel cover screws.

Dimensions:		L	W	H	Rating:
mm:		401	406	120	<b>Ingress Protection (EN 60529):</b> IP 66/67
inch:		15.8	16	4.7	<b>Impact Resistance (EN 50102):</b> IK 08
Materials:					<b>Electrical insulation:</b> Totally insulated
<b>Material:</b>		GRP			<b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes
<b>Base colour:</b>		RAL 7001			<b>UV resistance:</b> UL 508
<b>Cover colour:</b>		RAL 7001			<b>Flammability Rating (UL 746 C 5):</b> UL 94 5V
<b>Cover screws material:</b>		Stainless steel			<b>Glow Wire Test (IEC 695-2-1) °C:</b> 960
<b>Gasket material:</b>		EPDM			<b>NEMA Class:</b> NEMA 1, 4, 4X, 12, 13
Temperatures:					Certificates:
<b>Short term:</b>		-50 ... 120 °C			
<b>Continuous:</b>		-40 ... 80 °C			
<b>Short term:</b>		-60 ... 250 °F			
<b>Continuous:</b>		-40 ... 175 °F			
Accessories:					
PM 4040		Mounting plate			
ARH 40		DIN-35 Mounting rail			
MRS 28541		Wall fastening lug set			
PH A & AH A/B		Hinge set			

